

Memorandum

SUBJECT:	Annual Close-Out Memo of Cumulative Traffic Mitigation Measures for the Oakland				
	Deputy City Administrator		Environmental Coordinator City of Oakland Bureau of Planning		
ТО	Betsy Lake	FROM	Corey Alvin		
DATE	March 31, 2020				

The purpose of this memo is to document compliance in 2020 regarding the cumulative traffic mitigation measures for the Oakland Army Base Project (OAB) contained in the Project's 2012 Addendum to the 2002 Oakland Army Base Reuse Redevelopment Plan Area Environmental Impact Report and Standard Conditions of Approval/Mitigation Monitoring and Reporting Program (SCA/MMRP) (approved in 2012, as revised in 2013).

There are two cumulative traffic mitigation measures (MMs) that were identified for completion in 2020 and were in fact completed: MM 3.16-17: West Grand Avenue & I-880 Frontage Road and MM 3.16-18: San Pablo Ave & Ashby Avenue.

MM 3.16-17: West Grand Avenue & I-880 Frontage Road

This measure requires optimized signalization and associated intersection improvements prior to issuance of the first certificate of occupancy in order to maintain the Level of Service (LOS) at LOS D or above. Prior to issuance of the first certificate of occupancy, the City determined that occupancy of the first warehouse at the OAB (PODS Warehouse at 55-75 Admiral Toney Way) would not result in truck volumes at levels that would degrade the LOS to below LOS D.¹ Based on this determination, the City issued the first certificate of occupancy in June 2018. Further, this intersection is within Caltrans jurisdiction, and as documented in the Kittleson memorandum,² per discussion with Caltrans no physical improvements were required, and regardless, the City of Oakland has no authority to implement this mitigation. Therefore, the Project's mitigation responsibilities for MM 3.16-17 are completed.

¹ The Air Quality Plan for Operation of the PODS warehouse dated May 9, 2018 states that the number of daily one-way vehicular trips to serve this warehouse would be 100 (truck and car trips combined). This number of trips compared to the 21,325 2012 Project PM peak hour trips that degraded the intersection from LOS C to LOS F, would not cause the LOS of the studied intersections to degrade to below LOS E. Also refer to Table 3.16-10 in the 2012 OAB Addendum for LOS information.

² Memorandum from Kittelson & Associates, August 1, 2013, subject: Caltrans Off-Site Intersection Mitigations. \\oakland\ceda\Redev\Library2\redevelopment\1- Army Base\CEQA and NEPA\05 SCA-MMRP Implementation\Traffic Mitigation Measures\Berkeley evaluation signal improv San Pablo & Ashby Ave 08-01-2013.pdf

MM 3.16-18: San Pablo Ave & Ashby Avenue

This measure requires optimized signalization and associated intersection improvements prior to issuance of the first certificate of occupancy in order to maintain the LOS at LOS D or above. As noted above, the first certificate of occupancy was issued June 2018 after the City determined that the LOS would not degrade to LOS E based on truck volume resulting from occupancy of the first warehouse at the OAB (PODS Warehouse at 55-75 Admiral Toney Way).³ Further, this intersection is within the City of Berkeley. Improvements to the intersection are under the jurisdiction of the City of Berkeley and Caltrans who will undertake improvements as deemed necessary by those two entities as noted in the Kittleson memorandum cited above. Regardless, the City of Oakland has no authority to implement this mitigation. Therefore, the Project's mitigation responsibilities for MM 3.16-18 are completed.

In conclusion, the Project's mitigation responsibilities for MM 3.16-17, MM 3.16-18 are complete. See also the Traffic Impact Compliance Matrix, attached.

³ See footnote 1.

	sures	tigation Measures	Off-Site Project-Level Traffic Mitigation			4
			The components of these mitigation measures were constructed by the joint venture (JV) contractor during the installation of the horizontal infrastructure from 2015-2019. Refer to Horizontal Infrastructure Compliance Report for more detail.		t n	
		Prior to approval of the PUD	Mitigation measures 3.16-5 to 3.16-14 require improvements to existing streets in the Port of Oakland and to the new streets shown in the OAB master site plan. MM 3.16-5 to 3.16-14 identified specific improvements such as widened shoulders, new sidewalks, bicycle lanes, etc.	design feature or incompatible uses	2019	-
MM's-	See 2019 compliance memo - Project Level Traffic MM's-Final Compliance Memo.pdf	٥	Mitigation Measures 3.16-5 to 3.16-14 - Locations for these mitigation measures are on Maritime Street and Burma Road: between West Grand & 7th Street and between Gateway Park and West Grand Avenue respectfully.	The project would directly or indirectly cause or expose roadway users to a permanent and substantial transportation hazard due to a new or existing physical		
	zontal Infrastructure	d During Horiz	On-Site Traffic Mitigations Measures Completed During Horizontal Infrastructure	On-S		
	Mitigation Status	Mitigation Monitoring	Mitigation Measures	Environmental Impact	Implementation Year	
	IMRP	n OAB SCA/MMRP	Traffic Mitigation Measures from OAB			

At t would interse to increse to increse to increse average average of Cocupancy or more; of average to increse of average average average to increse of average avera	At a sti which Downt cause i degrac LOS E) At issuance of first Certificate of Occupancy	Implementation Year
At two intersections, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio exceeds 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable).	At a study, signalized intersection which is located outside the Downtown area, the Project would cause the level of service (LOS) to degrade to worse than LOS D (i.e., LOS E)	Environmental Impact
Mitigation Measure 3-16-3: 7th Street & Harrison Street - To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. The project sponsor shall fund, prepare, and install the approved plans and improvements.	Mitigation Measure 3.16-2: San Pablo Avenue & Ashby Avenue - To implement this measure, the Project Sponsor shall coordinate with City of Berkeley and Caltrans, and shall fund, prepare, and install the improvements consistent with City of Berkeley and/or Caltrans standards. Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group.	Mitigation Measures
At issuance of first Certificate of Occupancy	At issuance of first Certificate of Occupancy	Mitigation Monitoring
See 2019 compliance memo - Project Level Traffic MM's - Final Compliance Memo.pdf	See 2019 compliance memo - Project Level Traffic MM's - Final Compliance Memo.pdf	Mitigation Status
Mitigation responsibility is completed.	Mitigation responsibility is completed.	Completion Status

Traffic Mitigation Measures from OAB SCA/MMRP		
Measures from OAB SCA/MM	3	
Measures from OAB SCA/MM	Mitigation	
from OAB SCA/MM	Measure	
B SCA/MM	trom	
3	OAB	
3	SCA/	
	3	֡

			The project sponsor shall fund, prepare, and install the approved plans and improvements.		8	
completed.		of Occupancy	To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval.			
Witigation	2 8	At issuance of	 Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. 	degrade to worse than LOS D (i.e., LOS E).	2020	7)
	See 2020 compliance memo – <u>Cumulative Level Traffic</u> MM's – 2020 Compliance Memo.docx		Mitigation Measure 3.16-17: West Grand Avenue & I-880 Frontage Road	Increased congestion at signalized intersection outside the downtown area causing the Level of Service to	-	
		npacts	Cumulative Traffic Impacts			-
Mitigation responsibility is completed.	See 2019 compliance memo - Project Level Traffic MIM's - Final Compliance Memo.pdf	At issuance of first Certificate of Occupancy	To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. The project sponsor shall fund, prepare, and install the approved plans and improvements.	would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio exceeds 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable).	At issuance of first Certificate of Occupancy	Ci Ci
Completion Status	Mitigation Status	Monitoring	wingation weasures	Environmental impact	Year	
		Mitigation			Implementation	
			0			

	Tallic Willigation Wicasares It of Control		
Implementation Environmental Impact Mitigar	Mitigation Measures Monitoring	ing Mitigation Status	Completion Status
One intersection located outside the downtown area, where the level of service is LOS E, the project would cause the total intersection average vehicle delay to increase by four (4) or more seconds, or degrade to worse than LOS E. (Year 2020) 7 2020 **Mitigation Measure 3.16-18: San Pablo Ave & Ashby **Optimize signal timing (i.e., adjust the allocation of intersection approach) for the PM peak of Coordinate the signal timing changes at this intersection approach for the PM peak of Coordinate the adjacent intersections that are in the same second coordinate with the City of Berkeley and Caltrans, and improvements.	• Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall coordinate with the City of Berkeley and Caltrans, and shall fund, prepare, and install the approved plans and improvements.	See 2020 compliance memo — Cumulative Level Traffic MM/s — 2020 Compliance Memo.docx ce of ficate ancy	Mitigation responsibility is completed.
Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). Eleven intersections Wheasure 3.16-24: West Frontage Road - Optimize signal timing (i.e., increase intersection approach) for the AM a with the adjacent intersections that occordination group coordination group coordination group plans specifications and estimates (Mitigation Measure 3.16-24: West Frontage Road - Optimize signal timing (i.e., increase intersection approach) for the AM a with the adjacent intersections that occordination group plans specifications and estimates (Mitigation Measure 3.16-24: West Frontage Road - Optimize signal timing (i.e., increase intersection approach) for the AM a with the adjacent intersections that are specifications and estimates (Mitigation Measure 3.16-24: West Frontage Road - Optimize signal timing (i.e., increase intersection approach) for the AM a with the adjacent intersections that are specifications and estimates (Mitigation Measure 3.16-1 that are standards to City of Oakland's Transpersection approvel plans specifications and approvel. Optimize signal timing (i.e., increase intersection of the critical moverable) approach) for the AM a with the adjacent intersections that are specifications and estimates (Mitigation Measure 3.16-1 that are standards to City of Oakland's Transpersection approach (Mitigation Measure 3.16-1 that are standards to City of Oakland's Transpersection approach (Mitigation Measure 3.16-1 that are standards to City of Oakland's Transpersection approach (Mitigation Measure 3.16-1 that are standards to City of	Mitigation Measure 3.16-24: West Grand Avenue & I-880 intersection may be required by Optimize signal timing (i.e., increase the traffic signal cycle length and adjust the allocation of green time for each intersection approach) for the AM and PM peak hours: Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. Mitigation at this intersection may be required by Year 2021. Investigation of the need for this mitigation shall be studied in 2021 and every three years the reafter until 2035 or until the mitigation measure is implemented, whichever occurs first.	at this This intersection is within Caltrans jurisdiction. Refer to 8/01/13 memorandum from Kittelson and Associates. by on of or this shall in every s until til the ed, occurs	Pending

12 2023		11 2022	Implementation Year	
			entation	
1000	Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	Environmental Impact	
	 Mitigation Measure 3.16-31: 12th Street & Brush Street - Optimize signal timing (i.e., increase the traffic signal cycle length to 120 seconds and adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation Measure 3.16-26: West Grand Avenue & Market Street - • Provide split phasing for northbound and southbound movements. • Optimize signal timing (i.e., increase the traffic signal cycle length to 120 seconds and adjust the allocation of green time for each intersection approach) for both the AM and PM peak hours. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	Mitigation Measures	Traffic Mitigation Measures from OAB
Mitigation at this	Mitigation at this intersection may be required by year 2023. Investigations of the need for this mitigation shall be studied in 2023 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation at this intersection may be required by year 2022. Investigations of the need for this mitigation shall be studied in 2022 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation Monitoring	n OAB SCA/WINKP
Track feasibility relative to AC Transit plans to install signal	Track feasibility relative to the Preliminary Draft Downtown Oakland Specific Plan has identified this intersection as a freeway crossing and corridor improvements including street design and signal improvements that support slower vehicular speeds and prioritize pedestrians. Improvements would also reallocate excess space from traffic lanes to other uses. This mitigation measure to increase LOS may therefore be considered infeasible. Need to monitor.	Track feasibility relative to the West Grand Avenue road diet at West Grand Avenue and Market Street as part of West Oakland Specific Plan- June 26th, 2014 – Council Resolution No. 85108 C.M.S. Paving scheduled for road diet. This mitigation measure to increase LOS may therefore be considered infeasible. Need to monitor.	Mitigation Status	INR
	Pending	Pending.	Completion Status	

14		
2025		Implementation Year
Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	Environmental Impact
 Mitigation Measure 3.16-30: 6th Street & Jackson Street - Optimize signal timing (i.e., increase the traffic signal cycle length to 80 seconds and adjust the allocation of green time for each intersection approach) for the AM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	• Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	Mitigation Measures
Mitigation at this intersection may be required by year 2025. Investigations of the need for this mitigation shall be studied in 2025 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	the need for this mitigation shall be studied in 2025 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation Monitoring
The intersection is within the jurisdiction of Caltrans. Track relative to jurisdiction and revised CEQA standards.	independently from vehicular traffic with dedicated and separate from motor vehicles, further de-emphasizing vehicle LOS at this intersection. Need to monitor the progress of the 27th Street Complete Streets Project and the Lakeside Family Streets Projects. This mitigation measure to increase LOS may therefore be considered infeasible. Need to monitor.	Mitigation Status
Pending		Completion Status

16	15	
2028	2026	Implementation Year
Three intersections located outside the Downtown area, which the project would cause the level of service (LOS) to degrade to worse than LOS D. (Year 2035)	Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	Environmental Impact
Mitigation Measure 3.16-19: West Grand Avenue & Maritime Street - Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	Mitigation Measure 3.16-27: West Grand Avenue & San Pablo Avenue - • Remove approximately seven (7) parking spaces on the south side of West Grand Avenue; add an eastbound through lane between San Pablo Avenue and Martin Luther King Jr. Way; and convert the eastbound right turn lane to a through-right combination lane. • Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the PM peak hour. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	Mitigation Measures
Mitigation at this intersection may be required by year 2028. Investigations of the need for this mitigation shall be studied in 2028 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation at this intersection may be required by year 2026. Investigations of the need for this mitigation shall be studied in 2026 and every three years thereafter or until the mitigation is measure is implemented whichever occurs first.	Mitigation Monitoring
Track feasibility relative to the Gateway Park Project, which was studied in 2018. No significant impact, based on LOS, due to the Gateway Park Project was found to exist so no mitigations are proposed. By 2028, a significant increase in bikes and pedestrians at this intersection is expected occur. This mitigation measure to upgrade LOS may be therefore be considered infeasible. Further monitoring of plan implementation is necessary to determine if it remains reasonably assumed an increase in bike and pedestrian activity would occur.	Track feasibility relative to AC Transit plans to install a Signal Transit Priority (TSP) system at this intersection to improve bus operations in dedicated travel lanes by prioritizing bus movement at this intersection and potentially decreasing the LOS of crossing traffic. Also, a road diet at this location may also be implemented as part of the West Grand Mobility Plan. This mitigation measure to increase LOS may therefore be considered infeasible. Need to monitor future AC Transit implementation of this system.	Mitigation Status
Pending	Pending	Completion Status

18 20	17 20	3
2030	2028	Implementation Year
At one intersection located within the Downtown area, the project would cause the LOS to degrade to worse than LOS E (Year 2035)	Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	Environmental Impact
Mitigation Measure 3.16-21: West Grand Avenue & Northgate Avenue - • Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for the AM peak hour. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	 Mitigation Measure 3.16-32: Powell Street & Hollis Street Provide protected plus permitted traffic signal phasing for the northbound and southbound Hollis Street movements. Optimize signal timing (i.e., adjust the allocation of green time for each intersection approach) for both the AM and PM peak hours. Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Emeryville's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements. 	Mitigation Measures Mon
Mitigation at this intersection may be required by year 2030. Investigations of the need for this mitigation shall be studied in 2030 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation at this intersection may be required by year 2028. Investigations of the need for this mitigation shall be studied in 2028 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation Monitoring
Track feasibility relative to the AC Transit plans to install a Signal Transit Priority (TSP) system at this intersection to improve transit systems by prioritizing bus movement at this intersection and potentially decreasing the LOS of crossing traffic. Need to monitor future AC Transit implementation of this system.	The intersection is within the City of Emeryville. Track relative to jurisdiction and revised CEQA standards.	Mitigation Status
Pending	Pending	Completion Status

Traffic Mitigation Measures from OAB SCA/MMRP

10		
2035	2032	Implementation Year
Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any-of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	Eleven intersections where the level of service is LOS F, the project would cause (a) the total intersection average vehicle delay to increase by two (2) or more seconds, or (b) an increase in average delay for any of the critical movements of four (4) seconds or more; or (c) the volume-to-capacity ("V/C") ratio increases 0.03 or more (but only if the delay values are greater than 120 seconds of average intersection delay as delay values over 120 seconds tend to increase exponentially and are then generally considered unreliable). (Year 2035)	Environmental Impact
• Optimize signal timing (i.e., increase the traffic signal cycle length to 80 seconds and adjust the allocation of green time for each intersection approach) for the PM peak hour. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	**Mitigation Measure 3.16-25: West Grand Avenue & Adeline Street - • Optimize signal timing (i.e., increase the traffic signal cycle length to 90 seconds and adjust the allocation of green time for each intersection approach) for the PM peak hour. • Coordinate the signal timing changes at this intersection with the adjacent intersections that are in the same signal coordination group. To implement this measure, the project sponsor shall submit plans specifications and estimates (PS&E) as detailed in Mitigation Measure 3.16-1 that are consistent with the City's standards to City of Oakland's Transportation Engineering Division for review and approval. The project sponsor shall fund, prepare, and install the approved plans and improvements.	Mitigation Measures
Mitigation at this intersection may be required by year 2035. Investigations of the need for this mitigation shall be studied in 2035 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation at this intersection may be required by year 2032. Investigations of the need for this mitigation shall be studied in 2032 and every three years thereafter or until the mitigation measure is implemented whichever occurs first.	Mitigation Monitoring
This intersection was improved as part of the Public Improvement Project; monitor whether signal timing changes are required in future condition. Refer to 8/01/13 memorandum from Kittelson and Associates.	Track feasibility relative to the West Grand road diet from Mandela to Market as part of West Oakland Specific Plan-June 26th, 2014 – Council Resolution No. 85108 C.M.S. Paving scheduled for road diet by converting traffic travel lanes to bike lanes. Implementation of this mitigation measure may therefore be considered infeasible as a result of the City Council approved plan to reduce the width of the intersection.	Mitigation Status
Pending	Pending	Completion Status

21

22